



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Q 80115
Mullist
for
filed
3/4/04

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03290601.8

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk



Anmeldung Nr:
Application no.: 03290601.8
Demande no:

Anmeldetag:
Date of filing: 11.03.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

ALCATEL
54, rue La Boétie
75008 Paris
FRANCE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

A remote monitoring method and system

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

G08B25/00

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT SE SI SK TR LI

Quermann & Richardt

Quermann & Richardt • Unter den Eichen 7 • D-65195 Wiesbaden

INPI
26 bis, rue de Saint Petersburg

75800 Paris cedex 08
FRANCE

Patentanwälte

European Patent Attorneys
European Trademark Attorneys

Diplom-Ingenieur
Helmut Quermann

Diplom-Ingenieur
Markus Richardt

11th March 2003
/MR

Attorney Docket ID alca.202.23 EP

Alcatel
54, rue la Boétie, F-75008 Paris

A remote monitoring method and system

Description

Field of the invention

- 5 The present invention relates to the field of remote monitoring systems and methods, and more particularly without limitation, to remote fire, smoke, motion and/or sound detection.

Background and prior art

Various remote premise-monitoring alarm systems are known from the prior art.

- 10 For example, US Patent No. 5,745,849 shows a combination of a cordless

telephone and a premise-monitoring alarm system which has a base unit, a cordless handset and one or more remote alarm detectors.

The alarm detectors can be generally either smoke detectors, motion detectors, or open-entry detectors. The base unit includes at least one interface for the public telephone network, and another interface for radio communication with the cordless handset. The base unit preferably also communicates with the remote alarm sensors across the same radio interface. The base unit includes telephone call circuitry to relay telephone calls between the public telephone network and the handset. The base unit also includes alarm processing circuitry to send an alarm warning to a central alarm-monitoring station in response to an alarm signal from a remote detector. The base unit has control circuitry that is configured such that if, during a telephone call, the base unit is given an alarm signal, the base unit will either (i) hang up the telephone call and call up the central alarm-monitoring station to give warning, or (ii) call up the central alarm-monitoring station on a second telephone line.

US Patent No. 6,271,752 shows a multi-access remote monitoring system for monitoring of a security surveillance area. The security surveillance area comprises a local computer system, a network interface, and a camera having a motion sensor. The local computer system is electronically connected via a camera adapter to the video camera so that video, sound, and motion sensor data can be transmitted from the camera to the local computer system, and instructions or other data can be transmitted from the local computer system to the camera. The local computer system is additionally connected to a computer network interface, which may be a modem, network card, or other communications hardware, used to connect to the communications network. The local computer system includes various components, including an audio/video coder/decoder, fixed storage means, operating system software, communications software, compression software, and application programming interface (API) software.

It is a common disadvantage of prior art remote monitoring systems that special, dedicated hardware is required at the site which is monitored. The present invention therefore aims to provide an improved remote monitoring method and system which enables to limit the hardware expenditure for the surveillance zone.

Summary of the invention

The present invention provides for a remote monitoring method which uses the wireless application protocol and the hypertext transfer protocol for transmitting a signal, such as an alarm, alert or warning signal, from the surveillance zone to at least one receiver. This requires only a sensor being coupled to a wireless module at the surveillance zone.

The occurrence of an event is communicated from the wireless module to a monitoring server by means of the wireless application protocol through a wireless application gateway. The server determines one or more receiver addresses for the signal and forwards the signal to the one or more receivers through a wireless application protocol gateway. For example, the wireless application protocol gateway sends a service loading message to the one or more receiving mobile terminals in order to transmit the signal.

The service loading (SL) content type has been defined in the wireless application protocol standard WAP-168-serviceload-20010731-a (<http://www.wmlclub.com/docs/especwap2.0/WAP-168-ServiceLoad-20010731-a.pdf>). The SL content type provides a means to convey a uniform resource identifier (URI) to a user agent in a mobile client. The client itself automatically loads the content indicated by that URI and executes it in the addressed user agent without user intervention when appropriate. Thus, the end-user will experience the service indicated by the URI as if it was pushed to the client and executed. By basically conveying only the URI of the service to the client the over-the-air message will be small. Hence, very modest requirements are placed on the bearer and on the clients ability to receive and store a SL if it is busy with other activities.

Instead of executing the service, SL provides a means to instruct the client to pre-cache the content indicated by the URI so it becomes readily available to the user agent and the client. It is also possible to control whether the loading of the service is to be carried out in a user-intrusive manner or not.

- 5 In accordance with a preferred embodiment of the invention the server instructs the gateway to push a SL to the mobile client using the push access protocol (PAP). The push initiator, i.e. the server, provides the SL with the URI to the wireless mark up language (WML) that is executed in the client's user agent. The gateway sends the SL to the mobile client using the push over-the-air
10 protocol (OTA). Next the mobile client receives the push containing the SL. The service which is indicated by the SL's URI is retrieved ('pulled') from the monitoring server via the gateway.

- For example data which is indicative of the circumstances of an event which has been detected is signalled from the sensor to the wireless module. This
15 data can include an identifier of the sensor, information on the kind of event, time information and/or other information. This information is sent from the wireless module through the wireless application protocol gateway to the monitoring server. There the data is stored and an URI is assigned to the data. This URI is sent to the mobile client as part of the SL. This enables the mobile
20 client to retrieve the data from the monitoring server by means of the URI. This is particularly advantageous as the user can get additional information on the circumstances of the event rather than just the warning or alert message.

Brief description of the drawings

- In the following preferred embodiments of the invention will be described in
25 greater detail by making references to the drawings in which:

Figure 1 is a block diagram of a wireless remote monitoring system,

Figure 2 is a block diagram of a hybrid wireless and wired remote monitoring system.

Detailed description

Figure 1 shows wireless remote monitoring system 100 comprising one or more monitoring sensors 102, 104, 106, ... at one or more surveillance areas. The sensors 102, 104, 106, ... are coupled to wireless module 108. For example wireless module 108 is coupled to a group of sensors of the same surveillance area. Alternatively there is a dedicated wireless module 108 for each one of the sensors 102, 104, 106, ... in order to prevent the effort of providing wired connections from multiple sensors to the wireless module 108.

- 10 Wireless module 108 has program 110 which generates a WAP request 112, when wireless module 108 receives an alarm signal from at least one of the sensors.

Wireless module 108 uses a transport layer such as GSM, GPRS, UMTS or another wireless transport layer to send the WAP request 112 over wireless network 114 to wireless application protocol (WAP) gateway 116.

Gateway 16 is coupled to monitoring server 118. Gateway 116 converts WAP request 112 to hypertext transfer protocol (HTTP) request 120 which it forwards to monitoring server 118.

- 20 Monitoring server 118 has database 122 for storing one or more receiver addresses of mobile clients for each sender address, i.e. for each wireless module 108 or alternatively for each one of the sensors 102, 104, 106, ... For example each one of the sensors has an Internet protocol (IP) address which serves as a sender address; alternatively an IP of the wireless module 108 serves as a sender address or a combination of the IP addresses of the sensor
25 which issued the alarm signal and the wireless module which has sent the WAP request containing the alarm message.

Further, monitoring server 118 has program 124 for querying database 122 and for storing of data contained in the HTTP request 120 in storage 126. Further

program 124 creates an uniform resource identifier (URI) for retrieval of the data which has been stored in storage 126.

Monitoring server 118 is coupled to WAP gateway 128. In response to receiving HTTP request 130 from monitoring server 118, gateway 128 sends SL132
5 which contains the URI of the data of the alarm message.

SL132 is sent to one or more receivers as retrieved from database 122, i.e. to one or more of the mobile clients 134, 136, 138, ... over wireless network 140.

In operation sensors 102, 104, 106,... monitor a surveillance area for the occurrence of an event, such as a fire, smoke, motion and/or sound. When an
10 event is detected by one of the sensors, such as sensor 102, the sensor outputs a corresponding alarm signal which is received by wireless module 108. Sensor 102 can provide additional data, such as the sensor ID of sensor 102 or its IP address, information on the type of event, the detection time etc

In response to the alarm signal program 110 of wireless module 108 is invoked.
15 Program 110 generates WAP request 112 which can contain the additional data which is delivered by sensor 102.

WAP request 112 is transmitted over wireless network 114 to gateway 116 where WAP request 112 is converted to a corresponding HTTP request 120. This HTTP request 120 is received by monitoring server 118. This invokes
20 program 124 which queries database 122 in order to determine the receiver address or the receiver addresses which are pre-assigned to the sender address of HTTP request 120. Further, the data which is contained in HTTP request 120 is stored by program 124 in storage 126 and a URI is assigned to the data.

25 Monitoring server 118 outputs HTTP request 130 containing the URI and the receiver address or receiver addresses. This way monitoring server 118 instructs gateway 128 to send SL 132 containing the URI to the respective mobile clients over wireless network 140. By means of the URI the receiving mobile clients can retrieve the data from storage 126.

Preferably gateway 128 sets the 'execute-high' parameter for SL 132 such that the SL service is carried out in a user-intrusive manner. This ensures that the user's attention is immediately drawn to the alarm signal.

5 Figure 2 shows an alternative hybrid embodiment of a remote monitoring system. Like elements in figures 1 and 2 are designated by the same reference numerals.

In addition to the embodiment of figure 1, remote monitoring system 100 of figure 2 contains wired system components, i.e. sensor 142, personal computer 144 and personal computer 146. Sensor 142 is wired to personal computer 144.

10 Personal computers 144 and 146 are connected to monitoring server 118 by means of wired connections, such as over the Internet. When sensor 142 detects an alarm situation it outputs a corresponding alarm signal which is received by personal computer 144 and transmitted to monitoring server 118.

15 In response monitoring server 118 determines the address of personal computer 146 and forwards the alarm message to this computer. In this instance a uniform resource locator (URL) is provided to personal computer 146 rather than a URI as HTTP is used as a transport protocol rather than WAP.

20 In order to identify the communication protocol which is to be used to send an alarm message to a receiver each receiver address which is stored in database 122 (cf. figure 1) can have an attributive data field for specification of the protocol which is to be used such as WAP or alternatively HTTP.

List of Reference Numerals

100	remote monitoring system
102	sensor
104	sensor
106	sensor
108	wireless module
110	program
112	WAP request
114	wireless interlock
116	gateway
118	monitoring server
120	HTTP request
122	database
124	program
126	storage
128	gateway
130	HTTP request
132	SL
134	mobile client
136	mobile client
138	mobile client
140	wireless network
142	sensor
144	personal computer
146	personal computer

c l a i m s

1. A remote monitoring method comprising the steps of:

- 5 - monitoring an occurrence of an event,
- providing a signal to a wireless module in response to the occurrence of the event,
- sending a wireless application protocol request being indicative of the occurrence of the event to a first gateway,
- 10 - converting the wireless application protocol request to a first hypertext transfer protocol request,
- sending of the first hypertext transfer protocol request to a server,
- determining at least one receiver address for the first hypertext transfer protocol request by the server,
- 15 - sending of a second hypertext transfer protocol request from the server to a second gateway,
- sending of a wireless application protocol service loading message to the at least one receiver from the gateway.
- 20 2. The method of claim 1, fire, smoke, motion and/or sound sensors being used for monitoring.
3. The method of claim 1, whereby the signal contains data being indicative of circumstances of the occurrence of the event, whereby the data is sent by means of the wireless application protocol request, and further
- 25 comprising storing of the data by the server and assigning a uniform resource identifier to the data, and sending of the uniform resource

identifier to the at least one receiver by means of the wireless application protocol service loading message.

4. The method of claim 1, the wireless application protocol service loading message being user intrusive.

- 5 5. A remote monitoring apparatus comprising:

- sensor means (102, 104, 106,...) for monitoring an occurrence of an event,
- a wireless module (108,...) being coupled to the sensor means, the sensor means being adapted to provide a signal to the wireless module in response to the occurrence of the event, and the wireless module being adapted to send a wireless application protocol request (112) being indicative of the occurrence of the event to a wireless application protocol gateway (116).

- 15 6. A remote monitoring server comprising:

- means (118, 124) for receiving of a first hypertext transfer protocol request (120) from a first wireless application protocol gateway (116), the first hypertext transfer protocol request being indicative of the occurrence of an event,
- means (122) for determining at least one receiver address for the first hypertext transfer protocol request,
- means (118, 124) for sending of a second hypertext transfer protocol request (130) to a second wireless application protocol gateway (128) in order to initiate a wireless application protocol service loading message (132) to be sent to the at least one receiver.

7. A remote monitoring system comprising:

- means (102, 104, 106,...) for monitoring an occurrence of an event and for providing a signal to a wireless module in response to the occurrence of the event,
 - 5 - means (108, 110) for sending a wireless application protocol request (112) being indicative of the occurrence of the event to a first gateway (116),
 - means (116) for converting the wireless application protocol request (112) to a first hypertext transfer protocol request (120),
 - 10 - means (116) for sending of the first hypertext transfer protocol request to a server (118),
 - means (122, 124) for determining at least one receiver address for the first hypertext transfer protocol request,
 - means (122, 124) for sending of a second hypertext transfer protocol request (130) to a second gateway (128),
 - 15 - means (128) for sending of a wireless application protocol service loading message (132) to the at least one receiver (134, 136, 138,...).
8. The remote monitoring system of claim 7, the means for monitoring comprising a fire, smoke, motion and/or sound sensor.
- 20
9. The remote monitoring system of claim 7, further comprising means for storing of data being indicative of circumstances of the occurrence of the event on the server and means for assigning of a uniform resource identifier (URI) to the data.

12

10. The remote monitoring system of claim 7, the second gateway being adapted to set an execute-high parameter for sending of the wireless application service loading message.




Fig. 1




Fig.2

1002

abstract**A remote monitoring method and system**

5 The present invention relates to a remote monitoring method comprising the steps of:

- monitoring an occurrence of an event,
- providing a signal to a wireless module in response to the occurrence of the event,
- 10 - sending a wireless application protocol request being indicative of the occurrence of the event to a first gateway,
- converting the wireless application protocol request to a first hypertext transfer protocol request,
- 15 - sending of the first hypertext transfer protocol request to a server,
- determining at least one receiver address for the first hypertext transfer protocol request by the server,
- sending of a second hypertext transfer protocol request from the server to a second gateway,
- 20 - sending of a wireless application protocol service loading message to the at least one receiver from the gateway.

(Figure 1)




Fig. 1